

Tab.2 Dimensions - Line pipe HOT ROLLING CPE MILL

Norms	Nominal	OD		WT		Weight		Lmax		Identification	
		in	mm	in	mm	lb/ft	kg/m	ft	m	STD/XS/XXS	Sch.
ASTM A53 & API 5L & ISO 3183	1/2	0.840	21.3	0.109	2.77	0.85	1.27	29.5	9	STD	40
				0.147	3.73	1.09	1.62			XS	80
	3/4	1.050	26.7	0.113	2.87	1.13	1.69	29.5	9	STD	40
				0.154	3.91	1.48	2.20			XS	80
	1	1.315	33.4	0.133	3.38	1.68	2.50	29.5	9	STD	40
				0.179	4.55	2.17	3.24			XS	80
				0.250	6.35	2.85	4.24				160
	1 1/4	1.660	42.2	0.140	3.56	2.27	3.39	29.5	9	STD	40
				0.191	4.85	3.00	4.47			XS	80
				0.250	6.35	3.77	5.61				160
	1 1/2	1.900	48.3	0.145	3.68	2.72	4.05	39.4	12	STD	40
				0.200	5.08	3.63	5.41			XS	80
				0.281	7.14	4.86	7.25				160
	2	2.375	60.3	0.154	3.91	3.66	5.44	39.4	12	STD	40
				0.172	4.37	4.05	6.03				
				0.188	4.78	4.40	6.54				
				0.218	5.54	5.03	7.48			XS	80
				0.250	6.35	5.68	8.45				
	2 1/2	2.875	73.0	0.216	5.49	6.14	9.14	39.4	12		
				0.250	6.35	7.02	10.44				
				0.276	7.01	7.67	11.41			XS	80
	3	3.500	88.9	0.216	5.49	7.58	11.29	39.4	12	STD	40
				0.300	7.62	10.26	15.27			XS	80
				0.438	11.13	14.34	21.35				160
3 1/2	4.000	101.6	0.226	5.74	9.12	13.57	39.4	12	STD	40	
			0.318	8.08	12.52	18.64			XS	80	
4	4.500	114.3	0.237	6.02	10.80	16.08	39.4	12	STD	40	
			0.337	8.56	15.00	22.32			XS	80	
			0.438	11.13	19.02	28.32				120	

Note: Lengths: 6m or 9m or 12m